

Product Specifications

FlashLink[®] RTL Prime 3G In-Transit Logger, Temperature, Humidity, Light, Shock

Measurement Range	-22°F to 158°F (-30°C to 70°C)
Temperature Accuracy	±0.9°F from 14°F to 113°F (±0.5°C from -10°C to 45°C) ±2°F (±1°C) other
Temperature Resolution	0.1 °F/°C
Humidity Measurement Range	5% to 95% RH
Humidity Accuracy	±5% from 20% to 80% RH, ±7% <20% and >80%
Light Sensor Range	0 to 1769 Lux, Dual Stage Sensor
Shock Measurement Range	0G to 8G
Data Capacity	28,800 data points
Logging Interval	10 minutes
Data Upload Interval	180 minutes (factory programmable)
Log Duration	90 days
GSM Network	3G: Band 1/2/4/5/8 Global coverage 2G: Quad band GSM 850/900/1800/1900 MHz
SIM	Internal Embedded (Global Data Roaming)
Power Source	Lithium-ion battery, meets UN38.3
Battery Life	90 Days
Battery Shelf Life	1 year
Logger Weight	3.63 oz (103 grams)
Logger Dimensions	2.58in x 4.01in x 0.73in (65.5mm x 103mm x 18.5mm)
Waterproof Rating	IP65
Certification	FCC, CE Mark, RoHS, WEEE, NIST traceable temperature accuracy
System Requirements	Logger requires cellular network connection to send data to secure cloud application. User requires PC or other Internet enabled device to view data online
Download Requirements	Micro USB to USB cable for download to PC or other USB enabled device that can read PDF files



Model	Trip Duration	Logging Interval	Data Upload Interval
22369	90-Day	10 Minutes	180 Minutes

- Monitor temperature, humidity, light and shock during transport and storage
- No need to open shipping box or vehicle door to read data
- Location data plotted on Google Maps
- Light sensor alert when box or vehicle doors open, for added security
- Shock sensor detects physical impact
- Data is automatically uploaded to 24/7 cloud service
- On-board memory records data every 10 minutes
- Option to download PDF report to PC with USB cable

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system.

SS 22369_2111

